

圆孔及球面外径型

select	Inquiry	Bearing Designation	Dimension [mm]				Basic load ratings (kN) Cr	Weight (Kg)
			d	D	Bi	Be		
GW208PPB6	1.188	3.1496	1.437	0.708	26200	0.72		
GW209PPB11	1.7811	3.3464	1.437	0.866	29200	0.64		
GW209PPB2	1.7717	3.3464	1.189	1.189	29200	0.65		
GW209PPB4	1.535	3.3464	1.189	1.189	29200	0.75		
GW210PPB2	1.938	3.5433	1.189	1.189	31500	0.71		
GW210PPB5	1.785	3.5433	1.189	1.189	31500	0.79		
GW211PPB10	1.938	3.937	1.311	1.311	39100	1.02		
GW211PPB2	2.188	3.937	1.311	1.311	39100	0.97		
GW211PPB9	2.194	3.937	1.311	0.984	39100	0.92		
W208PPB2	1.5005	3.1496	1.689	0.708	26200	0.72		
W208PPB23	1.5005	3.1496	1.689	1.189	26200	0.68		
W208PPB4	1.188	3.1496	1.189	1.189	26200	0.72		
W208PPB6	1.188	3.1496	1.437	0.708	26200	0.72		
W208PPB7	1	3.1496	1.189	0.708	26200	0.64		
W209PPB11	1.7811	3.3464	1.437	0.866	29200	0.64		
W209PPB2	1.7717	3.3464	1.189	1.189	29200	0.65		
W209PPB4	1.535	3.3464	1.189	1.189	29200	0.75		
W210PPB2	1.938	3.5433	1.189	1.189	31500	0.71		
W210PPB5	1.785	3.5433	1.189	1.189	31500	0.79		
W211PPB2	2.188	3.937	1.311	1.311	39100	0.97		